

PRODUCT SPECIFICATION

HandPRO SERIES 7100 CLEAN CLASS NITRILE GLOVES

300mm (12") Length

ISO Class 5 Compatible

Powder-Free

White Color

Finger-Textured

Ambidextrous

Non-Sterile

Beaded Long Cuff





QUALITY & CONFORMITY

- Manufactured under ISO 13485, CAN/CSA ISO 13485, ISO 9001and US FDA QSR Quality Management System
- Conforms to Council Directive 89/686/EEC
- Conforms to PPE Regulation (EU) 2016/425
- Conforms to the following additional test standards:

IEST-RP-CC005.4	Recommended Practice for Cleanroom Gloves
ASTM D412	Tensile Properties of Vulcanized Rubbers
ASTM D5151-99	Standard Test for Detection of Holes in Medical Gloves
ASTM D573	Accelerated Aging for Nitrile (at 70° C for 166hr)

PERFORMANCE REQUIREMENTS

Characteristic	Inspection Level	AQL
Freedom from Holes	G1	2.5
Visual Defects (Major)	G1	2.5
Visual Defects (Minor)	G1	4.0
Physical Properties	S2	4.0
Physical Dimensions	S2	4.0

PHYSICAL DIMENSIONS

Size	X-Small (5/6)	Small (6/7)	Medium (7/8)	Large (8/9)	X-Large (9/10)
Palm Width ± 5 mm	76	86	101	111	119
Glove Length (mm)	Minimum 295 (Typical Value 302~305)				
Thickness (mm) Cuff (25 ± 5 mm from bead) Palm (center of palm) Finger (13 ± 3 mm from tip)	Manufacturing Minimum 0.08 0.10 0.12		Typica 0.08 [,] 0.10 [,] 0.14 [,]	~0.09 ~0.11	

PHYSICAL PROPERTIES

	Before Aging		After Aging		
Test	Manufacturing Minimum	Typical Value	Manufacturing Minimum	Typical Value	
Tensile Strength (MPa)	14	23.6~28.1	14	28.8~37.8	
Ultimate Elongation	500%	540~580%	400%	540~560%	
Force at Break	6.0 N	-	6.0 N	-	

CLEANLINESS SPECIFICATION

Particulates (0.5-20 µm)	<1500 particles/cm ²	Non Volatile Residue	<5 µg/cm ²
Anions µg/cm²			
Bromide Chloride Fluoride	<0.05 <0.3 <0.01	Nitrate Phosphate Sulfate	<0.5 <0.01 <0.3

ELECTRICAL PROPERTIES

HandPRO 7100 is a static dissipative glove in-use.

PRODUCT NUMBERS

Size	Item #	Case Quantity
X-Small	7100	1000
Small	7101	1000
Medium	7102	1000
Large	7103	1000
X-Large	7104	1000

PACKAGING

A 50 glove stack is placed into the right side of a plain bag, and another 50 gloves are placed on the left side of the same plain bag. The plain bag is sealed and placed into another outer bag. The outer bag is sealed. Ten packed outer bags are placed into a carton box with a carton liner. Carton liners are twist tie wrapped and carton is sealed with transparent tape. Outer bags and cartons are stamped with a lot number.

SHELF LIFE & STORAGE

Three years from date of manufacture. Store in a cool, dry place away from direct sunlight.

Manufactured in Malaysia for Hourglass International, Inc.

The information on this document is a guideline of typical values and characteristics of the product.

- Hourglass-Intl.com
 (800) 277-0994
 hourglass-international-inc
- hourglassinternationalinc

MourglassIntl

The specifications provided reflect the minimum acceptable requirements of the ASTM and FDA where applicable. Actual testing results are available upon request. Gloves offered by Hourglass International, Inc. meet or exceed these physical requirements. Independent laboratory test results are available upon request.

Your Protection Is Our Purpose

