# **HG1341**

# Hook and Loop Heel Grounder

# Heel grounders provide ESD grounding protection for staff on the move.

The HG1341 is constructed from durable materials and features a classic hook & loop closure.

These heel grounders connect the person wearing them to ground via a proper floor mat or flooring material. Wearing the conductive ribbon inside the shoe or sock assures proper electrical contact with the user. The ribbon connects to the conductive rubber to complete the circuit between the operator and the static controlled floor or mat.

A buried 1 meg ohm resistor is standard. Heel grounders are worn on both feet to provide consistent grounding while in motion.

Meets or exceeds requirements of ANSI ESD-S20.20.



### **Features**

- Hook and Loop Closure
- Buried Resistor
- 1.25" Cup Design

#### **Specifications:**

#### **Part Numbers:**

Resistor: 1 meg ohm (+/- 5%

tolerance), buried

HG1341:

Heel Grounder, Hook

and Loop, 1 meg

Color: Blue hook and loop,

Black/White rubber

Rubber Exterior: <10e5 ohms, 1.25"

wide

Ribbon: Conductive yarn in

gray polyester

ribbon

## **Applications:**

Heel grounders provide a path-to-ground for personal that must be mobile. They must be used in conjunction with an ESD floor or mat.

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.