

50 SERIES ESD CLEANROOM VINYL



Super Heavy Duty 300 lbs, Capacity, 2.5" High Resilient Density Foam for Better Comfort, Rubber Edge Banding Protection on Seat & Back


| MODEL | Upholstery Type | Height | Seat | Back | Footring | | Drag | Caster |
|--------|-----------------|------------|-------------|-------------|----------|-------|-------|--------|
| | | Adjustment | Dimensions | Dimensions | | | Chain | |
| 50-VCD | ESD-Cleanroom | 19''-27'' | 18"W x 17"D | 15"W x 12"H | 18" | Black | Yes | 1 |
| | Vinyl | | | | | Nylon | | |
| 52-VCD | ESD-Cleanroom | 17''-22'' | 18"W x 17"D | 15"W x 12"H | No | Black | Yes | 1 |
| | Vinyl | | | | | Nylon | | |

Conductive Cleanroom Seating Features:

Industrial Seating[™] conductive seating insures a safe, static-clear work area. All IS[™] conductive seating models are equipped with conductive seat cushions, Back cushions, as well as all metal parts and the IS[™] dual resistance system.

Isstat Group IV Vinyls ESD

- Surface Resistence: 10⁷ to 10⁹ Ohms per Square.
- Flamability: Pass California Tech Bulletin 117
- Carbon Filled Inner Layer





| Controls | Description | | |
|----------|---|--|--|
| DLC | Height and Back Tilt (This control has two levers for seat height and back angle adjustment and back height adjustment with knob | | |
| ST | Height and Seat and Back Tilt (This control has two levers, one for height adjust ment and the other for Seat and Back tilt adjustment and back height with knob | | |
| FLC | Three Lever for Individual Lift (Height lever adjustment, seat tilt adjustment ba tilt adjustment back adjustment with knob and a seat tension knob | | |



FR04

FR05

FR06

| Footring | Description | |
|----------|---|--|
| FR04 | Knobless Nylon Footring 18" | |
| | The Footring is Loosened and Tightened by Turning the Outer Ring. (option for models 20S, 45, 50 and 60) | |
| FR05 | Knobless Aluminum with Steel Ring 20" | |
| | The Footring is Loosened and Tightened by Turning the Outer Footring. (option for models 10, 20M and 20W) | |
| FR06 | Nylon Center with Steel Ring, Footring 18" (option for models 20S, 45, 50 and 60) | |



| Arms | Description |
|----------|---|
| TF-BX-C | Fixed Height and Width, with Chrome Arm Frames & ESD Arm Pads |
| TA-BX-C | Fixed Height and Adjustable Width, with Chrome Arm Frames & ESD Arm Pads |
| таа-вх-с | Adjustable Height and Adjustable Width, with Chrome Arm Frames & ESD Arm Pads |



| Caster | Description | |
|--------|--|--|
| 1B | Braking Caster , Recommended where Chairs may roll to easily when is Not Oc- cupied | |
| 1U | Soft Urethane Caster, Recommended on Tile, Cement and other Hard Surfaces | |
| 1UB | Soft Urethane Braking Caster, Recommended for reduce Mobility when is Not Occupied | |
| 2 | Nylon Glide, Recommended for use in areas where requiring limited mobility | |