


Lightweight

Features & Benefits: NuTech™ is a strong, yet lightweight innovative material that will protect your personnel from grime, dirt and particulates. These coveralls are designed to keep the wearer clean and comfortable all day. Pocketless to help control items entering and leaving the work area. Coveralls have a tapered collar neckline and a front zipper for easy donning and doffing.

Construction Details: Two designs are available: our standard coverall with elastic wrist & ankle and attached hood & boot version.


Elastic wrist & ankle, serged seams

Size	Part No.	Color	Case
S/M	CV-64022-2	White	25
L/XL	CV-64022-4	White	25
2X/3X	CV-64022-6	White	25
4X/5X	CV-64022-8	White	25



Elastic hood, wrist & ankle, SureGrip® boots, serged seams

Size	Part No.	Color	Case
S/M	CV-64B92-2	White	25
L/XL	CV-64B92-4	White	25
2X/3X	CV-64B92-6	White	25
4X/5X	CV-64B92-8	White	25



Dimensions

Size	Body (A)	Chest (B)	Sleeve (C)	Leg (D)
S/M	37 1/2"	24 1/4"	34"	28 1/2"
L/XL	40"	27"	36 1/2"	30"
2X/3X	43"	32"	38"	32"
4X/5X	43 1/2"	33 1/2"	42"	33"

Suggested Applications for Use



Automotive, Construction, General Manufacturing, Maintenance/Janitorial, Paint Spray, Warehouse and more.

NuTech™ Material Physical Properties

Bacterial Filtration Efficiency ASTM F2101	N/A	Ball Burst Strength ASTM D3787 (lbs)	12.96	COF (Coefficient of Friction) ASTM D1894 Static Kinetic	SureGrip® Boots 0.58 0.63
Delta P Breathability MIL-M-36954C (mm H ₂ O/cm ²)	>103.6	General Tensile ASTM D5034 (MD/TD)	17.41 / 12.85	Helmke Drum IEST-RP-CC003.3	Category I
Hydrostatic Resistance ASTM D751 (psi)	N/T	Mass/Unit Area ASTM D3776 (g/m ²)	51.2	Mullen Burst Strength ASTM D3786 (psi)	120
Puncture Propagation Tear Resistance (lbs) ASTM D2582 (MD/TD)	7.3 / 7.3	Synthetic Blood Penetration ASTM F1670	N/T	Trapezoid Tearing Strength (lbs) ASTM D5587 (MD/TD)	8.16/ 5.73
Water Resistance Impact Penetration AATCC Method 42	None Seen	Water Vapor Transmission ASTM E96 (gm/day-m ²)	373.91	Test results provided by an independent third party testing laboratory.	



N/A - Not Applicable N/T - Not tested

As more fully set forth in the AlphaProTech Terms and Conditions of Sale, because conditions of use are out of AlphaProTech's control, AlphaProTech makes no warranties, expressed or implied, and assumes no liability as to the performance of these products for a particular use.

Rev. New 07/17