



www.wearwell.com

Static Dissipative Anti-Fatigue Anti Fatigue Mats

Group 791



Static Dissipative Anti-Fatigue is an ideal ergonomic standing solution for manufacturing, pharmaceutical, and commercial areas where [static electricity](#) can pose a problem. What makes this product such a standout is the homogeneous carbon layer, which assures the speedy dissipation of static. Add to that our exclusive Nitricell sponge base, and you've got a star performer that lasts for years while providing unparalleled ergonomic benefits. Each mat includes an attached grounding snap.

NOTE: Mats must be grounded with a ground cord ([793-Cord](#)) and users must wear a heel grounder ([793-Heel](#))

- EOS/ESD S7.1: 1×10^6 to 1×10^{10}
- NFSI Certified
- "Best" sponge base
- Nitricell sponge base delivers 2X the resilience and 3X the life of typical sponges
- Lay-flat design and up to 20% more standing area than look-alikes
- Overall thickness 1/2" (13 mm)

Learn more about ESD flooring and matting in our blog - [ESD 101: Everything You Need to Know About ESD Mats, Flooring, and Work Surfaces](#).

Type	Anti-Fatigue Matting
Suitable Environment	Dry
Customization Level	C1 - Custom Length
Solid or Drainage	Solid
Compound	PVC Surface With Nitrile Infused Sponge
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .62 / Wet: COF = .17
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: RTT= 1×10^6 to 1×10^{10}
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
791.12x2x3GY	715411441747	Gray	0.5	2' x 3'	Y	EA
791.12x3x5GY	715411442287	Gray	0.5	3' x 5'	Y	EA
791.12x3x75GY	715411442454	Gray	0.5	3' x 75'	N	RL

