



4018 Staticide® Acrylic Floor Finish

Low Cost Protection Against ESD

Staticide® 4018 Acrylic Floor Finish offers static protection at a reasonable price. This economical formula leaves a durable, glossy finish that can last up to six months with proper maintenance. This ESD polish is a popular choice for companies that require frequent cleaning.

Easy to apply and maintain, Staticide® 4018 Acrylic Floor Finish leaves floors with a surface resistance of 10^8 - 10^9 ohms, complying with ANSI/ESD S20.20 guidelines. This water-based formula is RoHS and REACH compliant, biodegradable, non-flammable, and free of acids, alkalis, ammonia, formaldehyde and phthalates.

Directions:

Clean floor and apply two thin coats of floor finish with a dedicated rayon mop. Wait one hour between coats. Consult application procedure for details and precise instructions.

Maintenance:

Sweep or damp mop daily to remove dirt. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use the 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.









Product #4018-1
4 gallons per case

Product #4018-5
5-gallon pail

Product #4018-2
54-gallon drum

Ideal for the following applications:

- Production areas
- Warehousing
- Shipping areas
- Electronics repair facilities

-  **Coverage: 1,500 - 2,000 square feet per gallon**
-  **Non-toxic; biodegradable**
-  **Non-volatile solids: 18± 5%**
-  **Strip cycle: 6 months**
-  **Suitable to use on vinyl, linoleum, and ceramic tiles**
-  **Surface resistivity: 10^8 – 10^9 ohms per square (average)**
-  **Low V.O.C.**
-  **Water-based acrylic**